

# U.S.SAWS™

## U.S.SAWS Heavy Duty Dust Buggy - Joint Clean-out

The Heavy Duty Dust Buggy is designed to clean-out existing control joints before filling or remove failing or deteriorated epoxy, polyurea, or polyurethane joint fillers. The joint clean-out saw cuts up to 2" deep with an 8" blade. Its up-cut rotation allows debris to be removed from joints as your moving forward. The polyurethane wheels help the Dust Buggy track perfectly straight. This model is made with a heavy-duty cast aluminum alloy chassis to hold up the most abusive environments.



Open Blade Option



Metabo Grinder



Pointer for Precision



Aluminum Frame

### Features

- Ideal for joint clean-out, joint filler removal, decorative concrete, and concrete cutting
- With the Tiger Tooth blades or PCD milling blade, this machine will remove polyurea joint filler
- Adjustable blade depth with up to 2" cutting depth (with 8" blade)
- Powered by a Metabo 15 Amp W24-230
- Up-cut blade rotation cleans debris out of the joint
- Durable and stable machine to allow for straight, accurate cuts
- Vacuum port allows for dust-free operation

| Model               | Heavy Duty Dust Buggy   |
|---------------------|-------------------------|
| Part Number         | SX13590                 |
| Grinder Make/ Model | Metabo W24-230          |
| Output Power        | 15 Amp Electric         |
| Max RPM             | 6,600                   |
| Power Requirements  | 115V, 60Hz              |
| Max Cutting Depth   | 2"                      |
| Blade Diameter      | 7" or 8"<br>Dry Diamond |

