U.S.SAWS

5" HAND- HELD CRACK CHASER



The 5" Crack chaser is a hand-held crack chasing saw designed to rout out random cracks before filling. This saw is also used for cutting repair patches in concrete surfaces where a dust-free environment is needed. It can also be used for joint clean-out and joint fill removal in areas where the larger joint clean-out saws will not fit. The full metal blade guard protects the operator, and the polycarbonate dust shroud is durable enough to hold up to abrasive concrete dust.

The premium 5" crack chaser is powered by a 5" Metabo WE15-125 grinder and the standard model is equipped with Metabo W11-125 grinder.

Features:

- Light-weight system for horizontal or vertical surface crack repair applications and cutting out mortar or grout joints
- When used with a vacuum system, controls dust for cleaner work area
- Cut up to 1-1/4" deep with a 5" blade
- · Uses dry diamond blades
- This saw can use a 4", 4.5", or 5" blade
- · Assembly includes a grinder, shroud, and adapter ring



POWERED BY METABO



BLADE SIGHT



DURABLE SHROUD



FITS 4" - 5" BLADES

CRACK CHASER MODEL	PREMIUM	STANDARD
Part Number	SX55010	SX55014
Grinder Make/Model	Metabo WEV15-125 QUICK HT	Metabo W11-125 QUICK HT
Power	13.5 AMP	11 AMP
RPM	2,800-9,600	11,000
Power Requirements	120V, 60Hz	120V, 60Hz
Max Cutting Depth	1-1/4"	1-1/4"
Blade Diameter	4", 4.5" or 5"	4", 4.5", or 5"
Blade Width	.090, .125, .187, .250, .375	.090, .125, .187, .250
Blade Arbor	7/8"	7/8"
Weight	16 lb	16 lb

^{*} Requires spacer (sold separately)



