

# U.S.SAWS™

## U.S.SAWS 5" Crack Chaser Assembly



The U.S.SAWS 5" Crack chaser is a hand-held crack chasing saw designed to rout out random cracks before filling. This saw is also used for cutting repair patches in concrete surfaces where a dust-free environment is needed. It can also be used for joint clean-out and joint fill removal in areas where the larger joint clean-out saws will not fit. The full metal blade guard protects the operator, and the dust shroud is durable enough to hold up to abrasive concrete dust.

The premium 5" crack chaser is powered by a 5" Metabo grinder WE15-125 and the standard model is equipped with Metabo W11-125 Electric Grinder. Excellent for cutting out mortar or grout joints. These are an easy way to upgrade your existing tool for dust control.

### Features:

- Small and light-weight system for horizontal or vertical surface crack repair applications and cutting out mortar or grout joints
- When used with a vacuum system, controls dust for cleaner work area
- 1-1/4" maximum cutting depth
- Uses dry diamond blades
- Standard and Premium models offered
- Assembly includes a grinder, shroud, and adapter ring

| Model              | Premium Tuc-Pointer          | Standard Tuc-Pointer        |
|--------------------|------------------------------|-----------------------------|
| Part Number        | SX55010                      | SX55014                     |
| Grinder Make/Model | Metabo WEV15-125 QUICK HT    | Metabo W11-125 QUICK HT     |
| Power              | 13.5 AMP                     | 11 AMP                      |
| RPM                | 2,800-9,600                  | 11,000                      |
| Power Requirements | 120V, 60Hz                   | 120V, 60Hz                  |
| Max Cutting Depth  | 1-1/4"                       | 1-1/4"                      |
| Blade Diameter     | 4", 4.5" or 5" Dry Diamond   | 4", 4.5", or 5" Dry Diamond |
| Blade Width        | .090, .125, .187, .250, .375 | .090, .125, .187, .250      |
| Blade Arbor        | 7/8"                         | 7/8"                        |
| Weight             | 15 lb                        | 15 lb                       |

\* Requires spacer (sold separately)

