

U.S.SAWS™

U.S.SAWS MC-800 Propane Joint Hog Saw



The MC-800P “Joint Hog” is a milling machine/saw is designed to remove up to 4” in width and 1-3/4” in depth of concrete to repair spalled joints. It can also be used for grooving, cutting inlays, and to prep for permanent line striping in floors. This machine uses closely spaced diamond blades to cut away deteriorated concrete and leaves a textured, clean surface that requires no additional chipping or cutting before making a repair or filling. Blades can be spaced at various widths to achieve multiple results. The “up-cut” direction of the blades ejects the concrete millings upwards, where a specialized “vacuum plenum” blade guard will collect the debris and dust.

Features:

- Powered by a “certified” Propane 16 HP Vanguard V-Twin engine with an electric start and a CO2 monitor
- Built on the U.S.SAWS JS Series frame
- Frame is fully box welded of high-quality heavy gauge steel
- Solid rear axle serves as the chassis’ lifting pivot point for a nearly indestructible platform



Depth Adjuster



Carbon Monoxide Monitor



Blade Spacers



Electric Start

| Model | MC-800 Joint Hog |
|-------------------------------------|--|
| Part Number | SX77160WC |
| Fuel Type | Propane |
| Power | 16 HP Vanguard V-Twin Certified Propane/ Electric Start |
| Tank | Vapor - 20 lb |
| Max Cutting Depth | 1-3/4” (8” Blade) Fully Adjustable |
| Max Cutting Width | up to 4” |
| Minimum Clearance from Wall (side) | 3” |
| Minimum Clearance from Wall (front) | 7” |
| Cutting Speed | 2.5 feet per minute at 2” wide 1” deep - full mill |
| Arbor | 1” with Drive Pin Hole |
| Blade Size | 8” |
| Blade Width | .125 & .150 |
| Dust Collector Size | 400+ CFM is recommended |
| Weight | 240 lb |

