

MARK-III DUST BUGGY



The Mark-III Dust Buggy is a revolutionary product that is changing the way we clean-out joints and cut concrete. The joint clean-out machine is the third generation of the famous "Dust Buggy." The Mark-III is designed to clean-out joints and cut remove existing joint filler faster and more accurately. A specially designed blade guard allows the operator to see the blade yet still covers 98% of it for excellent dust control. The handle was redesigned for more stability, adjustable height, and rotates to get closer to walls or racks. The joint clean-out saw cuts up to 2" deep. The concrete clean-out saw fully complies with ANSI diamond blade speed regulations.

Production rates vary, but a good operator can easily clean out 10,000 linear feet of new, unfilled joints in an 8-hour shift.

Features


- Electric, portable joint clean-out saw ideal for joint clean-out, joint filler removal, decorative concrete, and concrete cutting
- Adjustable blade depth with up to 2" cutting depth with 8" blade
- Powered by a Metabo 15 Amp 24-230
- Up-cut blade rotation cleans debris out of the joint
- Solid aluminum chassis provides a durable and stable machine to allow for straight, accurate cuts
- Vacuum port allows for dust-free operation



EQUIPPED WITH
METABO



ALUMINUM ALLOY
CHASSIS



MAGNETIC SWITCH



ADJUSTABLE DEPTH

MARK-III DUST BUGGY SPECIFICATIONS

Part Number	SX13800
Grinder Make/ Model	Metabo W24-230
Output Power	15 Amp Electric
Max RPM	6,600
Power Requirements	115V, 60Hz
Max Cutting Depth	2"
Blade Diameter	7" or 8" Dry Diamond
Blade Width	.090", .125", .250"
Blade Arbor	7/8"
Dust Collector Size	200 CFM
Weight	51 lb

